

## KUBOTA SERIES



# KUBOTA

## PERFORMANCE DATA KUBOTA

Specifications 50Hz 400-230V					General specifications								
GENSETS	Prime Power		Standby Power		Engine type	CyL	Bore	Stroke	DSPL	Fuel Cons.	Gov	Silent Type Compact Version	
	kW	kVA	kW	kVA								Dimension LxWxH	Weight
	kW	kVA	kW	kVA		mm	mm	L		g/kw.h		mm	kg
AJ8KB	6	8	6.6	8	D905-E2BG	3L	72	73.6	0.898	244	Electric	1750x900x1100	650
AJ10KB	7.5	9	8.3	10	D1105-E2BG	3L	78	78.4	1.123	247	Electric	1900x900x1100	710
AJ13KB	8.8	11	9.7	12	V1505-E2BG	4L	78	78.4	1.498	247	Electric	2000x900x1100	760
AJ16KB	10	13	11	14	D1703-E2BG	4L	87	92.4	1.647	233	Electric	2000x900x1100	780
AJ22KB	15	19	16.5	21	V2203-E2BG	4L	87	92.4	2.197	233	Electric	2200x900x1150	920
AJ25KB	18	23	19.8	25	V2003-T-E2BG	4L	83	92.4	1.999	233	Electric	2200x900x1150	1020
AJ30KB	22	28	24.2	30	V3300-E2BG2	4L	98	110	3.318	243	Electric	2280x950x1250	1100
AJ42KB	28	35	30.8	39	V3300-T-E2BG2	4L	98	110	3.318	236	Electric	2280x950x1250	1150